

Datenblatt für Artikel: LID14851--

10112FA/B/W SCHWARZ LED 12W WW IP40 230V

Einbaudownlight, inklusive Treiber



Produktinfo

12W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 250mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Lichtstrom (lm)	720
Lichtfarbe	warmweiß
Farbtemperatur (K)	3000
Farbwiedergabeindex Ra	≥80
Lebensdauer	30.000h
Dimmbar	nein
Schutzklasse	II
Schutzart	IP40
Leuchtmittel inkl.	ja
Fassung	LED Platine
Ausstrahlwinkel (°)	120
Systemeffizienz (lm/W)	60
Leistungsfaktor	0,9

Technische Daten - Fortsetzung

Leistung (W)	12
Betriebsgerät	LED Treiber
Betriebsspannung AC (V)	220-240
Frequenz (Hz)	50/60
Montage	Deckeneinbau
Ausschnitt (mm)	Ø 155
Einbautiefe mm (mm)	50
Farbe	schwarz
Material	Acryl Kunststoff Alu Druckguss
Durchmesser (mm)	173
Optionales Zubehör	LID16949--
AUSSCHNITT mm	Ø 155

Maßbild: 10112FA/B/W SCHWARZ LED 12W WW IP40 230V



Artikeltabelle

BEZEICHNUNG	BEST.NR.
10112FA/B/W SCHWARZ LED 12W WW IP40 230V Einbaudownlight, inklusive Treiber	LID14851
Optionales Zubehör	
050180E FAST Kabel VERBINDER 32A 2x3-port	LID16949