

Datenblatt für Artikel: LID15056--

7829/W LED STRIP 24V WW 5m ROLL

9,6W/m IP20

Dimmbar, ohne 24V Treiber



Produktinfo

Flexible LED light strip, with SMD2216 LEDs, 140LEDs/meter, 9,6W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 5cm (7-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Lichtfarbe	warmweiß
Farbtemperatur (K)	3000
Farbwiedergabeindex Ra	≥90
Dimmbar	Abhängig vom Treiber ja
Schutzklasse	III
Schutzart	IP20
EEK	F
Energieeffizienzklasse	F
Leuchtenart	LED Strip
Leuchtmittel inkl.	ja
Fassung	LED Platine

Technische Daten - Fortsetzung

Systemeffizienz (lm/W)	90
Betriebsgerät	Muss separat bestellt werden
Betriebsspannung DC (V)	24
Eingangsspannung DC (V)	24
Ausgangsspannung DC (V)	24
Montage	Deckenanbau Wandanbau Bodenanbau
Optionales Zubehör	LID 14188--
Lichtstrom/m (lm/m)	864

Maßbild: 7829/W LED STRIP 24V WW 5m ROLL 9,6W/m IP20



Artikeltabelle

BEZEICHNUNG	BEST.NR.
7829/W LED STRIP 24V WW 5m ROLL 9,6W/m IP20 Dimmbar, ohne 24V Treiber	LID15056
Optionales Zubehör	
20030 FERNBEDIENUNG FÜR DIMMING LED STRIPS & LAMPS 12/24V zum Dimmen jeder konstanten Spannung 12V / 24V LED, einschließlich LED-Streifen, LED-Lampen, LED-Module. 50 Meter Reichweite, 2 Speichereinstellungen, Dimmen durch Berührung. 3 Kanäle x 3A	LID14188