

Datenblatt für Artikel: LID16707--

7848/W FLEX TILE 24V DC WW 10W IP20

240x480mm



Produktinfo

Flexible tile, 10W ideal for cover walls and columns. Supplied in 480mmx240mm pcs in white PCB and double adhesive tape for a better fixing. Complete with 2pcs power supply cable and 2pcs tile connectors. Connect max up to 10pcs with one driver. Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Lichtstrom (lm)	850
Lichtfarbe	warmweiß
Farbtemperatur (K)	3000
Farbwiedergabeindex Ra	≥90
Dimmbar	Abhängig vom Treiber ja
Schutzklasse	III
Schutzart	IP20
Leuchtenart	LED Strip
Leuchtmittel inkl.	ja
Fassung	LED Platine
Systemeffizienz (lm/W)	85
Leistung (W)	10

Technische Daten - Fortsetzung

Betriebsgerät	Muss separat bestellt werden
Betriebsspannung DC (V)	24
Eingangsspannung DC (V)	24
Montage	Deckenanbau Wandanbau Bodenanbau
Länge (mm)	480
Breite (mm)	240
Optionales Zubehör	LID16949--
Lichtstrom/m (lm/m)	850

Artikeltabelle

BEZEICHNUNG	BEST.NR.
7848/W FLEX TILE 24V DC WW 10W IP20 240x480mm	LID16707
Optionales Zubehör	
050180E FAST Kabel VERBINDER 32A 2x3-port	LID16949