

Datenblatt für Artikel: LID17296--

50140BW/W/V WEISS 40W CCTV 60x60cm EINBAU PANEL BACKLIT IP65

3000K-4000K-5700K, Complete with IP65 950mA driver



Produktinfo

60x60 backlit IP65 recessed CCT Variable LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications. Complete with 950mA driver. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Nettolänge (mm)	595,00
Nettobreite (mm)	595,00
Nettohöhe (mm)	35,00
Nettogewicht (kg)	2,17
Leuchtenart	LED Panel
Farbe	weiß
Material	Stahl Aluminium
Betriebsspannung AC (V)	220-240
Eingangsspannung AC (V)	220-240
Betriebsstrom mA (mA)	950
Eingangsstrom (A)	0,95
Fassung	LED Platine

Technische Daten - Fortsetzung

Systemeffizienz (lm/W)	100
Leistung (W)	40
Lichtfarbe	warmweiß neutralweiß kaltweiß
Farbtemperatur (K)	4000 3000 5700
Farbwiedergabeindex Ra	≥80
Lichtstrom (lm)	4000
Dimmbar	nein
Schutzklasse	II
Schutzart	IP65
Einbautiefe mm (mm)	60
LxBxH mm	595x595x35

Maßbild: 50140BW/W/V WEISS 40W CCTV 60x60cm EINBAU PANEL BACKLIT IP65



BEZEICHNUNG	BEST.NR.
50140BW/W/V WEISS 40W CCTV 60x60cm EINBAU PANEL BACKLIT IP65 3000K-4000K-5700K, Complete with IP65 950mA driver	LID17296