

Datenblatt für Artikel: LID17787--

38150BU/B/V SCHWARZ 48x SPOTS 40W 34° UGR17 + UPLIGHT 22W

Direct (20/30/40W) 34° / indirect (16/20/25W) 120°, 3m cable



Produktinfo

CCT and Power variable 40W UGR17 Linear system with 48 LED spots and uplight for suspended installation, ideal for offices. Complete with 2 x power variable drivers. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Nettolänge (mm)	1.300,00
Nettobreite (mm)	35,00
Nettohöhe (mm)	70,00
Farbe	schwarz
Material	Aluminium
Ausstrahlwinkel (°)	34/120
Blendungsfaktor (UGR)	<17
Betriebsgerät	LED Treiber
Betriebsspannung AC (V)	220-240
Eingangsspannung AC (V)	220-240
Fassung	LED Platine
Systemeffizienz (lm/W)	95

Technische Daten - Fortsetzung

Leistung (W)	40 30 20
Lichtfarbe	warmweiß neutralweiß kaltweiß
Farbtemperatur (K)	5000 4000 3000
Farbwiedergabeindex Ra	≥90
Lichtstrom (lm)	max. 1800/3800
Dimmbar	nein
Schutzklasse	I
Schutzart	IP20
Durchmesser (mm)	68
LxBxH mm	1300x35x70

Maßbild: 38150BU/B/V SCHWARZ 48x SPOTS 40W 34° UGR17 + UPLIGHT 22W



BEZEICHNUNG	BEST.NR.
38150BU/B/V SCHWARZ 48x SPOTS 40W 34° UGR17 + UPLIGHT 22W	LID17787
Direct (20/30/40W) 34° / indirect (16/20/25W) 120°, 3m cable	